

SMART LINE

BX1 - AMPLIFICADOR DE POTÊNCIA STEREO HIGH END 2X105 W/8 Ohms



Acabamentos	EAN
Preto	3760179291322
Branco	3760179291339

POWER OUTPUT 8 ohms 2x105W
 POWER OUTPUT 4 ohms 2x150W
 FREQUENCY RESPONSE (-3dB) 10Hz-50kHz
 DISTORSION < 0,03%
 S/N RATIO > 100 dB
 CHANNEL SEPARATION > 70 dB
 INPUT IMPEDANCE UNBALANCED 20KΩ
 INPUT IMPEDANCE BALANCED 38KΩ
 AC INPUT 115-230V
 POWER CONSUMPTION MAX <450W
 TRANSFORMER(S) 1
 DIMENSIONS H.160 x l.230 x D.309mm
 NET WEIGHT / GROSS WEIGHT 8,5kg 9,2kg

Preço (UN.)
€ 999,00

BX2 - AMPLIFICADOR DE POTÊNCIA MONO HIGH END 1X215 W/8 Ohms



Acabamentos	EAN
Preto	3760179291551
Branco	3760179291568

POWER OUTPUT - 8 Ohms : 1 x 215W
 FREQUENCY RESPONSE (-3dB) 10Hz-50kHz
 DISTORSION < 0,008%
 S/N RATIO = 105dB
 INPUT IMPEDANCE (UNBALANCED) 47KΩ
 INPUT IMPEDANCE (BALANCED) 47KΩ
 STANDBY POWER CONSUMPTION 0,45W
 GAIN 20dB
 AC INPUT 115-230V
 TRANSFORMER(S) 1
 DIMENSIONS OF THE AMPLIFIER H.115x l.230x D.280
 DIMENSIONS OF THE CARTONS H.240x l.320x D.390
 NET WEIGHT / GROSS WEIGHT 8,4 / 9,4 kg

Preço (UN.)
€ 999,00

UX1 - PRÉ AMPLIFICADOR C/ DAC, STREAMER E TRANSPORTE DE CD



Acabamentos	EAN
Preto	3760 179 291360
Branco	3760179291377

OUTPUT LEVEL Unbalanced 2 volts
 OUTPUT LEVEL balanced 4 volts
 FREQUENCY RESPONSE (+/-3dB) 20Hz - 45 kHz
 DISTORTION < 0.005%
 OUTPUT IMPEDANCE 10KΩ
 CHANNEL SEPARATION > 110dB
 S/N RATIO > 110dB
 DAC DIGITAL AUDIO 32bit-768kHz AK4490
 DIGITAL AUDIO PCM TRANSCELVER AK4118
 USB AUDIO / DSD XMOX XU208-256
 AC INPUT 115 or 230V
 POWER CONSUMPTION MAX Max 30W
 DIMENSIONS H. 130 x l. 230 x D. 310
 NET WEIGHT / GROSS WEIGHT 3,8 kg / 5,4 kg
 2.4G Wi-Fi network compatibility: IEEE 802.11b/g/n
 Wi-Fi transmitter frequency range: 2412 - 2472MHz (2.4GHz ISM Band, USA 11 Channels, Europe and others 13 Channels)
 Wi-Fi transmitter power: <20dBm (EIRP)
 Wi-Fi modulation: OFDM, DSSS, DBPSK, DQPSK, CCK, 16QAM, 64QAM

Preço (UN.)
€ 999,00

PX1 - PRÉ AMPLIFICADOR DUAL MONO COM DAC



Acabamentos	EAN
Preto	3760179291438
Branco	3760179291421

DIGITAL OPT. & COAX. INPUTS : 8 (6 Optical / 2 Coaxial)
 USB-B INPUT : XMOX asynchronous PC/MAC
 USB-A : YES / iPod/iPhone compatible
 AES/EBU INPUT : YES
 XFTB01 BT INPUT : YES Digital
 HEADPHONES INPUTS : 2
 DIGITAL OPTICAL/COAXIAL OUPUTS : 1/1
 ANALOG BAL/UNBAL OUPUTS : 1/1
 DIR DIGITAL AUDIO AKMAK4118 24Bits/up to 192kHz low jitter
 DAC WM8740 WOLFSON 24Bits/up to 192 kHz low jitter
 DIMENSIONS : H.129 x 230 x 325 mm

Preço (UN.)
€ 999,00

CLASSIC LINE

Amplificadores Integrados

X-I50BT - AMPLIFICADOR INTEGRADO COM BLUETOOTH



O amplificador integrado dispõe de várias entradas analógicas e também uma USB; Inclui um recetor de Bluetooth permitindo a ligação com dispositivos como tablets ou smartphones; potência de 2x50W a 8 ohms.

Acabamentos EAN
PRETO 3760179291186

Preço (UN.)
€ 450,00

X-i75 - AMPLIFICADOR INTEGRADO DE 2 X 75 W (8 Ohm) , DAC E BLUETOOTH



Power 8 Ω : 2x75W RMS; Power 4 Ω : 2x110W RMS
Frequency response (-3dB) 10Hz-35kHz; Tone Control +/- 10 dB; Distorsion < 0,1%;
Signal/Noise ratio > 90 dB; Channel Separation > 70 dB; Input Impedance 47KΩ;
Phono Input Impedance 47KΩ; Digital audio Converter AK4113 low jitter; Converter 24bit-192kHz;
USB B Converter Wolfson WM8740; X-MOS Asynchronous; In Level (CD/AUX...) < 300mV;
In Level Amplifier < 1,1V; Phono MM Input Level 2,5mV;
Bluetooth Module APTX - AAC (Optional module : X-FTB01)
AC Input 115-230V; Power Consumption : 300W (X-i75); Transformer (1)
Dimensions (cm) H12 cm x W.43 cm x D.32 cm
Net Weight : 8,6 kg (X-i75)

Acabamentos EAN
Preto 3760179291247

Preço (UN.)
€ 690,00

CLASSIC A10 - AMPLIFICADOR INTEGRADO COM ESTÁGIO A VÁVULAS E DAC INTEGRADO



POWER OUTPUT 8Ω, 4Ω and 2,66Ω 130W, 190W and 250W
OUTPUT LEVEL Unbal. (max vol.) 9 volts
FREQUENCY RESP. (+/--3dB) 20Hz - 80 kHz
DISTORTION < 0.006% @1KHz/1W < 0.02%@32W
SIGNAL TO NOISE HN 98dB
OUTPUT IMPEDANCE 10KΩ
DAC DIGITAL AUDIO AKM AK4490 (32bit - 768kHz)
DIGITAL AUDIO PCM TRANSCIEVER AK4118
INTERFACE DE RECEPTION USB/DSD
* Optical input supporting : 24bit - 96kHz PCM
* Coaxial input supporting : 24bit - 192kHz PCM
* USB audio PCM input supporting 24bit/32bit 44,1kHz - 384kHz
* USB audio PCM input supporting 2.8MHz (DSD64)-DOP/5.6MHz,
(DSD128)-DOP/11.2MHz (DSD 256)-DOP
AC INPUT 115/230V 50/60Hz
POWER CONSUMPTION MAX Max 900W
DIMENSIONS H. 175 x l. 385 x D. 430
NET WEIGHT 14,5 kg

Acabamentos EAN
Preto 3760179291988

Preço (UN.)
€ 1.790,00

CLASSIC A12 - AMPLIFICADOR INTEGRADO COM ESTÁGIO A VÁVULAS E DAC INTEGRADO



POWER OUTPUT 8Ω, 4Ω 190W, 280W
 OUTPUT LEVEL Unbal. (max vol.) 9 volts
 FREQUENCY RESP. (+/-3dB) 10Hz - 35 kHz
 DISTORTION < 0.007%
 SIGNAL TO NOISE HN 103dB
 OUTPUT IMPEDANCE 10KΩ
 DAC DIGITAL AUDIO PCM 1796
 INTERFACE DE RECEPTION USB/DSD
 * Optical input supporting : 24bit - 96kHz PCM
 * Coaxial input supporting : 24bit - 192kHz PCM
 * USB audio PCM input supporting 24bit/32bit 44,1kHz - 384kHz
 * USB audio PCM input supporting 2.8MHz (DSD64)-DOP/5.6MHz,
 (DSD128)-DOP/11.2MHz (DSD 256)-DOP
 AC INPUT 115/230V 50/60Hz
 POWER CONSUMPTION MAX Max 900W
 DIMENSIONS H. 195 x l. 430 x D. 455
 NET WEIGHT 17,9 kg

Acabamentos EAN
 Preto 3760179292367

Preço (UN.)
€ 2.690,00

X-11100 - AMPLIFICADOR INTEGRADO DE HIGH END COM DAC



POWER OUTPUT : 2x220W / 8Ω 2x400W / 4Ω
 FREQUENCY RESPONSE : (-3dB) 10Hz-70kHz
 TONE CONTROL : +/- 10 dB
 DISTORSION : < 0,025%
 S/N RATIO : > 102 dB
 CHANNEL SEPARATION : > 75 dB
 INPUT IMPEDANCE : 47KΩ Unbal. / bal. 47KΩ
 DAC DIGITAL AUDIO : BurrBrown PCM1796
 CONVERTER 24bit-192kHz USB B DAC : XMOS USB3318 / 24bits 192kHz
 Adaptive for playback / asynchronous for record
 IN LEVEL (CD/AUX...) : 500mV
 INPUT LEVEL PHONO MM : 7mV
 AC INPUT : 115-230V
 POWER CONSUMPTION MAX : <700W (StandBy < 0,5W)
 TRANSFORMER(S) : 1 (700VA)
 DIMENSIONS : H.210 x l.430 x D.476
 NET WEIGHT / GROSS WEIGHT : 21,4 kg

Acabamentos EAN
 Preto 3760179291872

Preço (UN.)
€ 3.590,00

AMPLIFICADORES CONNECTED

Amplificadores Integrados

PLAYSTREAM A1/XFTB - AMPLIFICADOR INTEGRADO 2 X 52W (6 Ohm)COM DAC , STREAMER, BLUETOOTH



Output Power - 52W
 Output Level - 9 volts
 Distorsion <0,004% @1KHz/24W
 Signal to Noise HN - 98dB
 Output Impedance 10K OHM
 DAC Digital Audio AKM PCM Ti
 AC Input - 115/230V 50/60Hz
 Power Consumption Max 180W
 Dimensions: (430x370x135)

Acabamentos EAN
 Preto 3760179292169

Preço (UN.)
€ 890,00

PLAYSTREAM A5/XFTB - AMPLIFICADOR INTEGRADO 2 X 80W (8 Ohm) COM DAC , STREAMER, BLUETOOTH



Acabamentos EAN
Preto 3760179291933

OUTPUT POWER 8Ω : 80W
OUTPUT LEVEL Unbalanced (max volume) : 9 volts
FREQUENCY RESPONSE (+/-3dB) : 20Hz - 80 kHz
DISTORTION < 0.004% @1kHz/24W
SIGNAL TO NOISE HN : 98dB
OUTPUT IMPEDANCE : 10KΩ
DAC DIGITAL : WM8740 or PCM1796
TRANSCEIVER : AK4113 or MS8416
* Optical input supporting : 24bit - 96kHz PCM
* Coaxial input supporting : 24bit - 192kHz PCM
AC INPUT : 115/230V 50/60Hz
POWER CONSUMPTION MAX : Max. 300W
DIMENSIONS : l. 430 x D. 370 x H. 135
NET/GROSS WEIGHT : 8,1Kg / 9,75Kg

Preço (UN.)
€ 1.190,00

PLAYSTREAM A7/XFTB -AMPLIFICADOR INTEGRADO 2 X 115W (8 Ohm) COM DAC , STREAMER, BLUETOOTH



Acabamentos EAN
Preto 3760179291940

OUTPUT POWER 8Ω : 115W
OUTPUT LEVEL unbalanced (max volume) : 9 volts
FREQUENCY RESPONSE (+/-3dB) : 20Hz - 80 kHz
DISTORTION < 0.004% @1kHz/24W
SIGNAL TO NOISE HN : 98dB
OUTPUT IMPEDANCE : 10KΩ
DAC DIGITAL AUDIO AKM : AK4490 or PCM1796
DIGITAL AUDIO PCM TRANSCEIVER : AK4118 or MS8416
* Optical input supporting : 24bit - 96kHz PCM
* Coaxial input supporting : 24bit - 192kHz PCM
AC INPUT : 115/230V 50/60Hz
POWER CONSUMPTION MAX : Max. 400W
DIMENSIONS : l. 430 x D. 370 x H. 135
NET/GROSS WEIGHT : 9,3Kg / 11,15Kg

Preço (UN.)
€ 1.490,00

CLASSIC RANGE

Amplificadores de Potência

X-A160 EVO - AMPLIFICADOR DE POTÊNCIA HIGH END STEREO 2 x 160W (8 Ohm)



Acabamentos EAN
Preto 3760179291957

Power output 8 Ω : 2 X 160 W RMS
Power output 4 Ω : 2 X 240 W RMS
Frequency response : 10 Hz - 80 kHz
Distortion < 0,07%
Signal/Noise ratio : > 120 dB
Channel separation > 80 dB
Input impedance : 20KΩ (Asymétrique)
Input impedance : 38KΩ (Symétrique)
AC Input : 115V/230V (Commutation automatique)
Standby power consumption : < 0,5W
Power consumption max : 500W
Power transformer : 700W
Toroidal transformer
Dimensions : H.16 cm x W.44 cm x D.42 cm
Net Weight : 19 kg

Preço (UN.)
€ 1.490,00

X-A220 EVO - AMPLIFICADOR DE POTÊNCIA HIGH END MONO 1 x 220W (8 Ohm)



Power output 8 Ω : 1 X 220 W RMS
 Power output 4 Ω : 1 X 350 W RMS
 Frequency response : 10 Hz - 80 kHz
 Distortion < 0,08%
 Signal/Noise ratio : > 100 dB
 Channel separation > 80 dB
 Input impedance : 32KΩ (Unbalanced)
 Input impedance : 38KΩ (Balanced)
 AC Input : 115V/230V (Auto switching)
 Standby power consumption : < 0,5W
 Power consumption max : 500W
 Power transformer : 700W
 Toroidal transformer
 Dimensions : H.20 cm x W.43 cm x D.45 cm
 Net Weight : 21 kg

Acabamentos EAN
 Preto

Preço (UN.)
€ 1.690,00

X-A600 - AMPLIFICADOR DE POTÊNCIA HIGH END STEREO 2 x 200W (8 Ohm)



Power output 8 Ω : 2 X 200 W RMS
 Power output 4 Ω : 2 X 300 W RMS
 Frequency response : 10 Hz - 80 kHz
 Distortion < 0,07%
 Signal/Noise ratio : > 113 dB
 Channel separation > 108 dB
 Input impedance : 20KΩ (Asymétrique)
 Input impedance : 38KΩ (Symétrique)
 AC Input : 115V/230V (Commutation automatique)
 Standby power consumption : < 0,5W
 Power consumption max : 575W
 Power transformer : 700VA
 Toroidal transformer
 Dimensions : H.21 cm x W.43,1 cm x D.46,4 cm
 Net Weight : 25 kg

Acabamentos EAN
 Preto 3760179292350

Preço (UN.)
€ 2.890,00

X-A1200 - AMPLIFICADOR DE POTÊNCIA HIGH END MONO 1 x 450 W (8 Ohm)



Power Output 8 Ω > 450 W
 Power Output 4 Ω > 700 W
 Frequency Response : 10 Hz - 80 kHz
 Distorsion : ≤ 0.003%
 S/N Ratio : ≥ 113db
 Input Impedance Unbalance : 32 kΩ
 Input Impedance Balance : 38 kΩ
 Standby Power Consumption : 0,45W
 Gain : 34,2db ± 1dB
 Power Transformer : 1000 W
 Stand By : 0,42 W
 Dimensions : H.23,5 cm W.43 cm D.45 cm
 Net Weight : 25,5 kg

Acabamentos EAN
 Preto 3760179291285

Preço (UN.)
€ 4.000,00

CLASSIC RANGE

Pré Amplificadores

X-P700 - PRÉ AMPLIFICADOR HIGH END DUAL MONO



Acabamentos EAN
Preto 3760179292206

MAX OUTPUT LEVEL UNBAL./BAL 10.5 +/-0.5dB
FREQUENCY RESPONSE 10Hz-150kHz
DISTORSION < 0,01%
S/N RATIO ≥ 110 dB
CHANNEL SEPARATION ≥ 100 dB
INPUT IMPEDANCE UNBALANCED 23KΩ
INPUT IMPEDANCE BALANCED 35KΩ
IN LEVEL (CD/AUX) < 500mV
INPUT LEVEL PHONO MM/MC 48dB/64dB
DAC ANALOG DEVICES CS8416
AUDIO RECEIVER CS8416
AC INPUT 110-230V
POWER CONSUMPTION MAX ≤ 30W
TRANSFORMER(S) 2
DIMENSIONS H. 15.5 x 1.44x D.43
NET WEIGHT / GROSS WEIGHT 14.2 / 15,6 kg

Preço (UN.)
€ 1.390,00

X-P1200 - PRÉ AMPLIFICADOR HIGH END COM DAC SIGMA DELTA



Acabamentos EAN
Preto 3760179292077

MAX OUTPUT LEVEL UNBAL./BAL 10.5 +/-0.5dB
FREQUENCY RESPONSE 10Hz-150kHz
DISTORSION < 0,01%
S/N RATIO ≥ 110 dB
CHANNEL SEPARATION ≥ 100 dB
INPUT IMPEDANCE UNBALANCED 23KΩ
INPUT IMPEDANCE BALANCED 35KΩ
IN LEVEL (CD/AUX) < 500mV
INPUT LEVEL PHONO MM/MC 48dB/64dB
DAC ANALOG DEVICES AD1955 (SIGMA DELTA)
AUDIO RECEIVER CS8416
AC INPUT 110-230V
POWER CONSUMPTION MAX ≤ 30W
TRANSFORMER(S) 2
DIMENSIONS H. 15.5 x 1.44x D.43
NET WEIGHT / GROSS WEIGHT 14.2 / 15,6 kg

Preço (UN.)
€ 3.500,00

CLASSIC RANGE

LEITORES DE CD INTEGRADOS E TRANSPORTES DE CD

X-CD7 LEITOR DE CD'S INTEGRADO



Acabamentos EAN
Preto 3760179291223

Output Level : 2V (unbalanced)
Output Level : 3,87V (balanced)
Frequency Response (+/-1db) : 20Hz à 20 kHz
Distorsion < 0.005%
Output Impedance : 10KΩ
Channel Separation : 105dB
Signal Noise ratio : 97 dB
Convertor Wolfson WM8761 : 24bit-192kHz
AC Input : 115V-230V
Power Consumption < 8W
Dimensions (H/W/D) 70x430x257mm
Net Weight : 4,95 kg

Preço (UN.)
€ 459,00

X-CD9 LEITOR DE CD'S INTEGRADO COM SAIDA A VÁLVULAS



Acabamentos EAN
Preto 3760179292398

Output Level : 2V (unbalanced)
Output Level : 3,87V (balanced)
Frequency Response (+/-1db) : 20Hz à 20 kHz
Distorsion < 0.005%
Output Impedance : 10KΩ
Channel Separation : 101dB
Signal Noise ratio : 103 dB
Oversampling : 24bit-192kHz
AC Input : 115V-230V
Power Consumption < 8W
Dimensions (H/W/D) 73x430x260mm
Net Weight : 5,15 kg

Preço (UN.)
€ 790,00

X-CD 1000 EVO LEITOR DE CD'S INTEGRADO



Acabamentos EAN
Preto 3760179292091

Output Level : 2V (unbalanced)
Output Level : 3,87V (balanced)
Frequency Response (+/-1db) : 20Hz à 20 kHz
Distorsion < 0.005%
Output Impedance : 10KΩ
Channel Separation : 101dB
Signal Noise ratio : 103 dB
AC Input : 115V-230V
Power Consumption < 30W
Dimensions (H/W/D) 109x430x372mm
Net Weight : 9,2 kg

Preço (UN.)
€ 1.290,00

X-D 500 TRANSPORTE DE CD'S



Acabamentos EAN
Preto 3760179291251

Output Level : 2V (unbalanced)
Output Level : 3,87V (balanced)
Compartmentalized CD Drive - Double supply
Oversampling : (24bit/96kHz - 24bit/192kHz)
AC Input : 115V-230V
Power Consumption < 30W
Dimensions (H/W/D) 109x43,1x372mm
Net Weight : 9,6 kg

Preço (UN.)
€ 990,00

Streamers & Bluetooth Receivers

X-Stream9 - MULTI MEDIA PLAYER COM STREAMING, DAC E LEITOR DE CD'S



Acabamentos EAN
Preto 3760179291384

OUTPUT LEVEL Unbalanced 2 volts; OUTPUT LEVEL balanced 4 volts
FREQUENCY RESPONSE (+/-3dB) 20Hz - 45 kHz; DISTORTION < 0.005%
OUTPUT IMPEDANCE 10KΩ; CHANNEL SEPARATION > 110dB
S/N RATIO > 110dB; DAC DIGITAL AUDIO 32bit-768kHz AK4490
DIGITAL AUDIO PCM TRANSCIEVER AK4118; USB AUDIO / DSD XMOS XU208-256
AC INPUT 115 or 230V; POWER CONSUMPTION MAX Max 30W
DIMENSIONS H. 130 x l. 230 x D. 310; NET WEIGHT / GROSS WEIGHT 3,8 kg / 5,4 kg
2.4G Wi-Fi network compatibility: IEEE 802.11b/g/n
Wi-Fi transmitter frequency range: 2412 - 2472MHz
(2.4GHz ISM Band, USA 11 Channels, Europe and others 13 Channels)
Wi-Fi transmitter power: <20dBm (EIRP)
Wi-Fi modulation: OFDM, DSSS, DBPSK, DQPSK, CCK, 16QAM, 64QAM

Preço (UN.)
€ 990,00

WTX-StreamTubes - STREAMER DE ALTA QUALIDADE COM ESTÁGIO A VÁLVULAS



SOLUTION Raytheon 5703/ Linkplay /Wolfson or TI
 STREAMING PC/MAC/NAS UPNP / DLNA / Airplay
 STREAMING SMARTPHONES & TABLETS Android or iOS Advance Playstreal app
 STREAMING SERVICE Spotify, Deezer, Tidal, Tune-In, Qobuz, Amazon Music, TuneIn, vTuner, etc.
 APPS Advance Playstream (free app)
 WIFI & INTERNET 802.11 b/g/n
 AUDIO FORMAT APE, FLAC, WAV, APPLE LOSSLESS ALAC, AAC, AAC-LC, HE-AAC, HE-AACv2, MP3
 (CBR/VBR 32 to 320kpps)
 INTERNET RADIO YES
 DAC BurrBrown PCM1796 24-bit, High Performance 192kHz
 ANALOG STEREO OUTPUT YES / RCA
 DIGITAL STEREO OUTPUT YES / OPTICAL 24-bit / 192kHz
 DIMENSIONS H.47 x l.130 x D.150mm * Specifications and features subject to modifications

Acabamentos EAN
 Preto 3760179292084

Preço (UN.)
€ 399,00

WTX1100 - RECEPTOR BLUETOOTH DE ALTA QUALIDADE



Solution : QCC / Cirrus Logic; BT : 5.0
 Codec : aptX, aptX HD, AAC, SBC
 DAC : CS4344 24-Bit/192kHz; Dynamic range 105dB
 Popguard technology; Low clock jitter
 Tri-core processing : DualCore 32-Bit
 SingleCore 120Mhz

Acabamentos EAN
 Preto 3760179291902

Preço (UN.)
€ 229,00

WTX-Microstream - STREAMER PLUG AND PLAY



STREAMING PC/MAC/NAS : YES; UPNP STREAMING SMARTPHONES & TABLETS : YES
 STREAMING SERVICE : YES - Spotify, Tidal, Tune-In, Qobuz, etc.
 AUXILIARY INPUT : YES; APPS Android & App store; WIFI 802.11 b/g/n
 AUDIO FORMAT - APE, FLAC, WAV, APPLE LOSSLESS - ALAC, AAC, AAC-LC, HE-AAC,
 - HE-AACv2, MP3 (CBR/VBR 32 to 320kpps) - WMA 48kHz/16bit or up to 192kHz/24bit
 INTERNET RADIO : YES - DAC - WOLFSON or ESS - 24-bit, High Performance 192kHz
 - Signal to noise ratio of 112dB
 DIMENSIONS H.75 x l.14 x D.49/55mm
 NET WEIGHT / GROSS WEIGHT ND

Acabamentos EAN
 Preto 3760179291414

Preço (UN.)
€ 149,00

WTX 700 EVO - RECEPTOR BLUETOOTH HD PLUG AND PLAY



Solution QCC
BT HD
Codec aptX, aptX HD, AAC, SBC
External DAC PCM Ti / Built-in
Audio interfaces 24-bit
Tri-core processing 32-bit
Blister dimensions : 205*135*40mm
Blister weight : 0,184 KG

Acabamentos

EAN

Preço (UN.)

Preto

3760179291865

€ 149,00

WTX500 - RECEPTOR BLUETOOTH PLUG AND PLAY



Use of apt-X Bluetooth Codec tested under these formats: AAC/WAV/FLAC/APE
Analog output
High level music restitution
Can be used with all the Bluetooth hand-held devices
Simple and Intuitive to implement

Output Level : 600 mV RMS
Output Impedance : 10 k Ω
Gain : 0 dB
Distorsion : 0,09 %

Dimensions max : H.5,5 cm x W.1,4 cm x D.6 cm
Weight : 24 g

Acabamentos

EAN

Preço (UN.)

Preto

3760179290660

€ 99,00

All in one

MY CONNECT 60 - SISTEMA ALL IN ONE COM STREAMER , CD , RADIO



POWER OUTPUT 48/70 Watts CLASS AB 4Ω/8Ω
OUTPUT LEVEL Unbalanced 2 volts
FREQUENCY RESPONSE (+/-3dB) 20Hz - 45 kHz
DISTORTION < 0.1%
OUTPUT IMPEDANCE 10KΩ
CHANNEL SEPARATION > 110dB
S/N RATIO > 92dB
DAC DIGITAL Ti PCMS1X
AC INPUT 115 or 230V
POWER CONSUMPTION MAX Max 30W
DIMENSIONS H. 136 x l. 265 x D. 385
NET WEIGHT 5,5 kg

Acabamentos

EAN

Preço (UN.)

Preto

3760179291926

€ 790,00

MyCast7 - SISTEMA AUDIÓFILO ALL IN ONE COM STREAMER , CD , RADIO HDMI ARC



Power Output 45Watts Class AB 60hM
Output Level Unbalanced 2 volts
Frequency Response (+/-3dB) 25Hz-45kHz
Distortion <0,1%
Output Impedance 10KOhM
Channel Separation > 105dB
S/N Ratio > 92 dB
DAC Digital Audio Wolfson PCM TI
AC INPUT 230V
Power Consumption Max 30W
Dimensions: H 136 x L265 x D385
Net Weight: 6,7 Kg

Acabamentos

EAN

Preço (UN.)

Preto

3760179292152

€ 699,00

MY CONNECT 150 - SISTEMA AUDIÓFILO ALL IN ONE COM ESTÁGIO A VÁLVULAS



POWER OUTPUT 80, 40 and 2,66Ω 130W, 190W and 250W CLASS AB
OUTPUT LEVEL Unbalanced (max volume) 9 volts
FREQUENCY RESPONSE (+/-3dB) 2 0Hz - 80 kHz
DISTORTION < 0.006% @1kHz/1W
SIGNAL TO NOISE HN 105dB
OUTPUT IMPEDANCE 10KΩ
CHANNEL SEPARATION > 110dB
DAC DIGITAL AUDIO AKM AK4490 (32bit - 768kHz)
DIGITAL AUDIO PCM TRANSCIEVER AK4118
INTERFACE DE RECEPTION USB/DSD
* Optical input supporting : 24bit - 96kHz PCM
* Coaxial input supporting : 24bit - 192kHz PCM
* USB audio PCM input supporting 24bit/32bit 44,1kHz - 384kHz
* USB audio PCM input supporting 2.8MHz (DSD64)-DOP/5.6MHz, (DSD128)-DOP/11.2MHz (DSD 256)-DOP
AC INPUT 115/230V 50/60Hz
TENSION SECTEUR
POWER CONSUMPTION MAX Max 900W
CONSOMMATION MAXIMALE
DIMENSIONS H. 170 x l. 371 x D. 430
NET WEIGHT 14,5 KG
Gross WEIGHT 17,2 KG

Acabamentos

EAN

Preço (UN.)

Preto

3760179291858

€ 2.199,00

MY CONNECT 250 - SISTEMA AUDIÓFILO ALL IN ONE COM ESTÁGIO A VÁLVULAS



POWER OUTPUT 80, 40 and 2,66Ω 190W, 280W CLASS AB
OUTPUT LEVEL Unbalanced (max volume) 9 volts
FREQUENCY RESPONSE (+/-3dB) 2 0Hz - 80 kHz
DISTORTION < 0.006% @1kHz/1W
SIGNAL TO NOISE HN 105dB
OUTPUT IMPEDANCE 10KΩ
CHANNEL SEPARATION > 110dB
DAC DIGITAL AUDIO AKM AK4490 (32bit - 768kHz)
DIGITAL AUDIO PCM TRANSCIEVER AK4118
INTERFACE DE RECEPTION USB/DSD
* Optical input supporting : 24bit - 96kHz PCM
* Coaxial input supporting : 24bit - 192kHz PCM
* USB audio PCM input supporting 24bit/32bit 44,1kHz - 384kHz
* USB audio PCM input supporting 2.8MHz (DSD64)-DOP/5.6MHz, (DSD128)-DOP/11.2MHz (DSD 256)-DOP
AC INPUT 115/230V 50/60Hz
TENSION SECTEUR
POWER CONSUMPTION MAX Max 900W
CONSOMMATION MAXIMALE
DIMENSIONS H. 170 x l. 371 x D. 430
NET WEIGHT 14,5 KG
Gross WEIGHT 17,2 KG

Acabamentos

EAN

Preço (UN.)

Preto

3760179292374

€ 2.990,00

Bluetooth Transmitter

HDT-800 - TRANMISSOR BLUETOOTH



Solution : CSR 8675
BT : 4.2
Codec : aptX, aptX HD, AAC, SBC
Processing : RISC + DSP Kalimba 24-bit/120Mhz
Dimensions : 70 x 66 x 20mm W/D/H

Acabamentos **EAN**
Preto 3760179292015

Preço (UN.)
€ 129,00

Colunas Wireless

AIR65 - COLUNAS ACTIVAS COM DAC E BLUETOOTH



System: 2 Ways
Drivers: 2 per speaker
Woofers/Med.: 13cm Rubber & paper
Tweeter: 2,5cm dome
Amplifier: 2x55W
Frequency of response: 45Hz-22kHz
DAC Wolfson: 24-bits/192kHz
Bluetooth solution: aptX QCC3008
Dimensions: H28,5 x D22,5 x L17cm (per speaker)
Weight: 4,3 kgs Master speaker / 3,7 Kgs Slave speaker

EAN
Branco/Madeira 3760179292213
Preto/Nogueira 3760179292237
Preto 3760179292107

Preço (Par)
€ 599,00

AIR 65 CONNECT - COLUNAS ACTIVAS COM DAC STREAMER E BLUETOOTH



System: 2 Ways
Drivers: 2 per speaker
Woofers/Med.: 13cm Rubber & paper
Tweeter: 2,5cm dome
Amplifier: 2x55W
Frequency of response: 45Hz-22kHz
DAC Wolfson: 24-bits/192kHz
Bluetooth solution: aptX QCC3008
Dimensions: H28,5 x D22,5 x L17cm (per speaker)
Weight: 4,3 kgs Master speaker / 3,7 Kgs Slave speaker

Acabamentos **EAN**
Branco/Madeira 3760179292220
Preto/Nogueira 3760179292244
Preto 3760179292114

Includes WTX-Microstream (wifi dongle)

Preço (Par)
€ 699,00