

Model	Hyphn
Sensitivity (2.83Vrms @ 1m)	86 dB
Recommended Amplifier Power (RMS into 4 Ohm, Music Signal)	200 - 1,600 W
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	800 W
Nominal Impedance	4 Ohm
Minimum Impedance (20Hz to 20kHz)	3.5 Ohm @ 2.2 kHz
Drive Unit Complement	4 x 8" (203 mm) RDT III Bass Driver 6 x 2" (50 mm) RDT III Midrange Driver 1 x MPD III Transducer
Frequency Response (In-room, -6dB)	18 Hz - 60 kHz
Maximum Peak SPL (single speaker @1m Z-Weighted)	129 dB
System Format	3-Way
Bass Alignment	Bass Reflex
Port Tuning Frequency	25 Hz
Crossover Frequencies	350 Hz, 3.7 kHz
External Dimensions (Inc. plinth) (H x W x D)	1392 x 502 x 520 mm (54 <sup>13/16</sup> x 19 <sup>3/4</sup> x 20 <sup>1/2</sup> " )
Weight (Inc. plinth, ex. packaging)	106.9 kg (235 lbs 10.7 oz)



Audio Advice

