

	TT level 1.1 Record Player + Tonearm 0–33–45 RPM electronic switchable Incl. Tone arm, Audio Technica 3600L cartridge, cover, record weight Base in transparent acrylic of black acrylic WxDxH 430 x 327 x 140 mm, 8 Kg	1.295€
	TT level 2.1 DC Record Player + Tonearm + Speedpod 0–33–45 RPM, control and fine adjustment via SpeedPod Incl. SpeedPod, tone arm, Audio Technica 3600L cartridge, cover, record weight Base in transparent acrylic of black acrylic WxDxH 430 x 327 x 152-162 mm, 8 Kg	1.795€
	TT level 3.1 Record Player + Tonearm SpeedPod option: Speed adjustment in 0.01 rpm steps 0–33–45 RPM, SpeedPod available as extra Incl Titanium tone arm, Audio Technica 3600L cartridge, cover, record weight Base in solid beech and black acrylic or solid walnut and black acrylic WxDxH 430 x 327 x 156 mm, 11 Kg	2.495€ 199€
	Automatic Arm Lifter Little Fwend Automatic Arm Lifter for Takumi. Lifts the arm at the end of the record. Supplied with two self-sticking steel discs for the Takumi base. The Little Fwend Arm Lifter sticks to the disc by the magnet in its base. Easy to install, easy to adjust. No friction in use.	229€
	Aka MC Aluminium cantilever / Bonded Tiny Spherical 5/20uM Square coil 4N OCC, impedance 5 ohm, Bandwidth 20-20.000Hz +/-2dB Output level 0.3mV, Channel separation > 24dB, Channel balance < 0.8dB Tracking force 1.4-2.2 gram, recommended force 1.8 gram, VTA 20 degrees Compliance 16 uM/mN, Weight 9 grams, recommended load 100-470 ohm	395€
	Kuro MC Boron cantilever / Nude Eliptical 6/15uM Square coil 4N OCC, impedance 5 ohm, Bandwidth 20-22.000Hz +/-2dB Output level 0.26mV, Channel separation > 25dB, Channel balance < 0.5dB Tracking force 1.6-2.2 gram, recommended force 1.8 gram, VTA 20 degrees Compliance 13 uM/mN, Weight 9 grams, recommended load 100-470 ohm	795€
	Shiro MC Boron cantilever / Nude Fine Eliptical 5/15uM Square coil 6N OCC, impedance 4.7 ohm, Bandwidth 20-25.000Hz +/-2dB Output level 0.26mV, Channel separation > 26dB, Channel balance < 0.3dB Tracking force 1.6-2.2 gram, recommended force 1.8 gram, VTA 20 degrees Compliance 13 uM/mN, Weight 9 grams, recommended load 100-330 ohm	1.295€
	Kin MC Ruby cantilever / Nude Fine Eliptical 5/15uM Square coil 6N OCC, impedance 4.7 ohm, Bandwidth 15-25.000Hz +/-2dB Output level 0.28mV, Channel separation > 28dB, Channel balance < 0.3dB Tracking force 1.6-2.0 gram, recommended force 1.8 gram, VTA 20 degrees Compliance 15 uM/mN, Weight 9 grams, recommended load 100-330 ohm	1.795€
	Myo MC Saphire cantilever / Nude Fine Eliptical 5/15uM Square coil 6N OCC, impedance 4.7 ohm, Bandwidth 15-28.000Hz +/-2dB Output level 0.28mV, Channel separation > 28dB, Channel balance < 0.3dB Tracking force 1.3-2.0 gram, recommended force 1.8 gram, VTA 20 degrees Compliance 16 uM/mN, Weight 9 grams, recommended load 100-330 ohm	2.495€